

**Project:**

**Note:**

**Type:**

**Quantity:**

**Model#:** C - MPT - 3818 - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_

## Features



- Black or Polished chrome faceplate (with a black housing), White faceplate (with white housing)
- Canopy comes without pendants (ordered separately)
- When ordered with pendants, canopy ships with pendants assembled and pre-installed on canopy
- Fabricated steel construction
- Powder coated paint finishes
- Driver located in canopy housing
- Damp location rated

## Specifications

- Input Voltage: 100-277 VAC 50/60Hz
- Dimming: TRIAC, ELV or 0-10V Dimmable
- For recommended dimmers see <https://www.blackjacklighting.com/dimming-information>

## Options

- Available with Integral or Remote driver
- Optional Lutron driver available
- Standard Finishes: BL-Matte Black, PC-Polished Chrome (with black housing) or WH-White (with white housing)
- Special Order Powder Coat Finishes (with black housing): BZ - Bronze, SG - Satin Gold or SS - Satin Silver



Pendants sold separately. For options see pages 2 and 3  
For driver information see page 4



## CANOPY ORDERING GUIDE

Series	Size/ Type	Finish	Power Supply	Wattage
C-MPT	3818			
	3818" 38" Length 18 Ports	<b>Standard</b> BL Matte Black PC Polished Chrome WH White <b>Spec. Order</b> BZ Bronze SG Satin Gold SS Satin Silver <b>Custom</b> CS Customer Specification	<b>Universal</b> UIN Integral (standard) REM Remote <b>Custom</b> C Customer Selection (consult factory)	40W 40 Watts 96W 96 Watts

Example: C-MPT-3818-BL-UIN- 40W (For driver information see pg 4)

## WATTAGE GUIDE










Pendant Watts	Ports	Recommended Driver
2W	18 Ports	40W
5W	12 Ports Max	96W
12W	Not Recommended	

For other variations consult factory




Pendants sold separately. For full specifications and ordering information see [www.Blackjacklighting.com](http://www.Blackjacklighting.com)

(# symbol indicates additional specification)


## Light Guide - 2W/ 87lm

 2" 5.08 cm 1" 2.54 cm	 5" 12.7 cm					 4" 10.2 cm	 7" 17.78 cm	 1" 2.54 cm
<b>SHORT FROSTED</b> SP-LGD-SF-01- #-MPC	<b>TALL CLEAR</b> SP-LGD-TC-01- #-MPC	<b>TALL FROSTED</b> SP-LGD-TF-01- #-MPC	<b>BUBBLE</b> SP-LGD-BU-01- #-MPC	<b>FILAMENT</b> SP-LGD-FL-01- #-MPC	<b>CANDLE</b> SP-LGD-CA-01- #-MPC	<b>A-LAMP</b> SP-LGD-AL-03- #-MPC	<b>GRADIENT</b> SP-LGD-GR-01- #-MPC	<b>MUSHROOM</b> SP-LGD-MU-01- #-MPC

## 3" Acrylic Globe - 2W / 87lm

 2" 3.3 cm 3" 7.6 cm		
<b>FROSTED</b> SP-GLS-FR-03-#-MPC	<b>CLEAR</b> SP-GLS-CL-03-#-MPC	<b>BUBBLE</b> SP-GLS-BU-03-#-MPC


## 3" Glass Globe - 2W/87lm

 2.5" 6.35 cm 3" 7.6 cm
<b>WHITE GLASS</b> SP-GGS-WH-03-#-MPC





## 5" Glass Globe - 2W/ 87lm

 2.5" 6.35 cm 5" 12.7 cm
<b>WHITE GLASS</b> SP-GGL-WH-05-#-MPC


## 5" Acrylic Globe - 5W/ 368lm

 3" 7.6 cm 5" 12.7 cm
<b>CLEAR</b> SP-GLL-CL-05-#-MPC

## Novo Tall - 5W/ 368lm

 18" 45.7 cm 1.25" 3.18 cm 2" 5.08 cm	 .75" 1.91 cm	 7.5" 19.05 cm	
<b>REFLECTOR RING</b> SP-NVT-RR-02-#-MPC	<b>LUMINOUS RING</b> SP-NVT-LR-02-#-MPC	<b>FROSTED DIFFUSER</b> SP-NVT-FR-02-#-MPC	<b>BUBBLE DIFFUSER</b> SP-NVT-BU-02-#-MPC





## Cone Tall - 2W/ 87lm

 40" 102 cm .375" .95 cm 2.5 cm
<b>TALL CONE w/ LUMINOUS RING</b> SP-COT-LR-01-#-MPC



## Cone Short - 2W/ 87lm

 10" 25.4 cm 1.25" 3.18 cm 2" 5.1 cm
<b>SHORT CONE w/ REFLECTOR RING</b> SP-COS-RR-02-#-MPC

## Novo Short - 5W/ 368lm

 3" 7.6 cm 1.25" 3.18 cm 2" 5.08 cm	 .75" 1.91 cm	 7.5" 19.05 cm	
<b>REFLECTOR RING</b> SP-NVS-RR-02-#-MPC	<b>LUMINOUS RING</b> SP-NVS-LR-02-#-MPC	<b>FROSTED DIFFUSER</b> SP-NVS-FR-02-#-MPC	<b>BUBBLE DIFFUSER</b> SP-NVS-BU-02-#-MPC

## Special Order Novo - 5W/ 368lm

 24" 61 cm .75" 1.91 cm 2" 5.08 cm	 36" 91.4 cm .75" 1.91 cm 2" 5.08 cm
<b>24" w/ LUMINOUS RING*</b> SP-NV2-LR-02-#-MPC	<b>36" w/ LUMINOUS RING*</b> SP-NV3-LR-02-#-MPC


Lumen values are delivered lumens

\* Special order only Novo 24" and 36" can be used with any Novo Tall or Novo Short diffuser

Pendants sold separately. For full specifications and ordering information see [www.Blackjacklighting.com](http://www.Blackjacklighting.com)

(# symbol indicates additional specification)

## 8" Glass Sphere - 2W/ 87lm



## 12" Glass Sphere - 5W/ 368lm



## 4" Bullet - 2W/ 87lm



## 8" Bullet - 5W/ 368lm



## Color Gel - 2W/ 87lm



## 10" Pill Box - 12W/ (Gold interior = 700lm , White interior = 800lm)



## 5" Velo - 2W/ 87lm



## 16" Domos - 12W/ (Gold interior = 700lm , White interior = 800lm)



Lumen values are delivered lumens


For more details and ordering information, consult factory

## I. Universal Drivers

Universal dimmable (TRIAC, ELV or 0-10V), Flicker-free dimming 100% to 2% (with optimal configuration), auto reset, short circuit, overload and thermal protection



Watts	Output Volts	Input Volts	Mounting	Comments
15W	24V	120V - 277V	- Integral	(27U)
20W	24V	120V - 277V	- Integral	(27U)
40W	24V	100V - 305V	- Integral	(27U)
60W	24V	120V - 277V	- Integral	(27U)
96W	24V	120V - 277V	- Integral	(27U)
60W	24V	120V - 277V	- Remote	(27U)
96W	24V	120V - 277V	- Remote	(27U)




## II. LUTRON Hi-Lume Drivers

Continuous flicker-free dimming, auto reset, short circuit, overload and thermal protection  
Compatible with most Lutron dimming control systems



Watts	Output Volts	Input Volts	Mounting	Comments
40W	24V	120V - 277V	- Inside Canopy	3 Wire (27E) Dims 100% - 1%
40W	24V	120V	- Inside Canopy	2 Wire (12T) Dims 100% - 1%
40W	24V	120V - 277V	- Remote	3 Wire (27E) Dims 100% - 1%
40W	24V	120V	- Remote	2 Wire (12T) Dims 100% - 1%
96W	24V	120V - 277V	- Remote	3 Wire (27E) Dims 100% - .1%



## ORDERING GUIDE

### Category

PS

PS Power Supply

### Type

94ST Standard (Universal)  
94LT Lutron  
94CS Customer Specification

### Watts

15W 15 Watts  
20W 20 Watts  
40W 40 Watts  
60W 60 Watts  
96W 96 Watts

### Dimming

12T TRIAC Dimming  
27U 120-277V/ Universal  
Dimming (TRIAC, ELV, 0-10V)  
27E 120-277V/ Lutron EcoSystem

### Mounting

IN Integral  
RE Remote

Example: PS-94ST-96W-27U-RE