

Project:

Type:

Quantity:

Note:

SKU#: DOM - 32P - - -

Description

Subtle, arching geometric forms with color and scale. Quality illumination delivered via screw-in bulb or integrated, highly-efficient LEDs. Fixture incorporates universal voltage input and universal dimming.

Features


- Available in in four exterior finish options, each with complimentary interior finishes
- Available standard with E26 socket (lamp not provided)
- Suspends 72" from the ceiling with a black power cord
- Optional integrated LED light kit with glass diffuser comes with a 12' black power cord and aircraft suspension cable
- Spun aluminum construction with a powder coated paint finish
- Damp location rated

Specifications

- Color Rendering Index: 90 CRI for all light kit options
- LED color temperature: 3000K for all light kit options
- Input Voltage: 120 VAC 50/60Hz (120V- 277VAC for integrated LED light kit options only)
- Wattage: 23w
- Delivered lumens: 1800lm
- Dimming: No dimming options for 12E light source. Integrated LED light kit upgrade features universal dimming (TRIAC/ ELV/
- Fixture weight: 4.9 lb. (2.2kg)
- For downloadable IES & LM79 files see Blackjacklighting.com
- For recommended dimmers see Blackjacklighting.com

Custom

- Upgradable to integrated LED light kit; includes 120-277VAC driver with universal dimming (TRIAC/ ELV/0-10V)
- Integrated LED light kit (comes standard in 3000K) upgradable to 4000K 90CRI color temperature



ORDERING GUIDE

Family	Size/Type	Finish
DOM	32P	
	32P 32" Pendant	BG Black w/ Gold Interior SW Satin Nickel w/ White interior

Example: DOM-32P-SW-12E-NAK

CUSTOM OPTIONS

Volts/Dimming	Color Temp.
12E	NAK
12E 120VAC, E26 screw-in socket 27U 120-277VAC, Universal Dimming (12E Standard)	NAK Color temp. option not available with 12E 30K 3000K (Standard with Integrated LED light kit) 40K 4000K (NAK Standard)