

**Project:**

**Note:**

**Type:**

**Quantity:**

**Model#:** C - MCR - 1003 - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_

## Features



- Black or Polished chrome faceplate (with a black housing), White faceplate (with white housing)
- Canopy comes without pendants (ordered separately)
- When ordered with pendants, canopy ships with pendants assembled and pre-installed on canopy
- Fabricated steel construction
- Powder coated paint finishes
- Driver located in canopy housing
- Damp location rated

## Specifications

- Input Voltage: 100-277 VAC 50/60Hz
- Dimming: TRIAC, ELV or 0-10V Dimmable
- For recommended dimmers see <https://www.blackjacklighting.com/dimming-information>

## Options

- Available with Integral or Remote driver
- Optional Lutron driver available
- Special Order Face Plate Finishes (with black housing): BZ - Bronze, SG - Satin Gold or SS - Satin Silver



Pendants sold separately. For options see pages 2 and 3  
For driver information see page 4



## CANOPY ORDERING GUIDE

Series	Size/ Type	Finish	Driver	Wattage
C-MCR	1003			
	1003" 10" Diameter 3 Ports	BL Matte Black PC Polished Chrome WH White BZ Bronze SG Satin Gold SS Satin Silver	Universal UIN Integral URE Remote Lutron LI2 Integral 2 Wire LI3 Integral 3 Wire LR2 Remote 2 Wire LR3 Remote 3 Wire	15W 15 Watts(not available in Lutron driver)(Integral only) 20W 20 Watts (Not available in Lutron Driver)(Integral only) 40W 40 Watts

Example: C-MCR-1003-BL-UIN-20W

(For driver information see pg 4)

## WATTAGE GUIDE


Pendant Watts	Ports	Recommended Driver
2W	3 Ports	15W
5W	3 Ports	20W
12W	3 Ports	40W

For other variations consult factory


Pendants sold separately. For full specifications and ordering information see [www.Blackjacklighting.com](http://www.Blackjacklighting.com)

(# symbol indicates additional specification)


## Light Guide - 2W/ 90lm




## 3" Acrylic Globe - 2W / 90lm




## 3" Glass Globe -2W/90lm




## 5" Glass Globe -2W/ 90lm




## 5" Acrylic Globe - 5W/ 400lm



## Novo Tall - 5W/ 400lm




## Cone Tall - 2W/ 90lm




## Cone Short - 5W/ 400lm



## Novo Short - 5W/ 400lm



## Special Order Novo - 5W/ 400lm




Lumen values are delivered lumens

\* Special order only Novo 24" and 36" can be used with any Novo Tall or Novo Short diffuser

Pendants sold separately. For full specifications and ordering information see [www.Blackjacklighting.com](http://www.Blackjacklighting.com)

(# symbol indicates additional specification)

## 8" Glass Sphere - 2W/ 90lm



## 12" Glass Sphere - 5W/ 400lm



## 4" Bullet - 2W/ 90lm



## 8" Bullet - 5W/ 400lm



## Color Gel - 2W/ 90lm



## 10" Pill Box - 12W/ (Gold interior = 700lm , White interior = 800lm)



## 5" Velo - 2W/ 90lm



## 16" Domos - 12W/ (Gold interior = 700lm , White interior = 800lm)



Lumen values are delivered lumens


For more details and ordering information, consult factory

## I. Universal Drivers

Universal dimmable (TRIAC, ELV or 0-10V), Flicker-free dimming 100% to 2% (with optimal configuration), auto reset, short circuit, overload and thermal protection



Capacity	Output	Input Voltage	Mounting
15W	24V	120V - 277V	<b>UIN</b> (Integral)
20W	24V	120V - 277V	<b>UIN</b> (Integral)
40W	24V	120V - 277V	<b>UIN</b> (Integral)
60W	24V	120V - 277V	<b>UIN</b> (Integral)
96W	24V	120V - 277V	<b>UIN</b> (Integral)
60W	24V	120V - 277V	<b>URE</b> (Remote)
96W	24V	120V - 277V	<b>URE</b> (Remote)




## II. LUTRON Hi-Lume Drivers

Continuous flicker-free dimming, auto reset, short circuit, overload and thermal protection  
Lutron LED drivers provide reliable, high-performance dimming and are guaranteed to work with Lutron controls, and are supported by Lutron customer service



Capacity	Output	Input Voltage	Mounting	Description
40W	24V	120V - 277V	<b>LI3</b> (Integral)	Hi-Lume 1% L3DA EcoSystem 3-wire
40W	24V	120V	<b>LI2</b> (Integral)	Hi-Lume 1% LTEA 2-wire 120V
40W	24V	120V - 277V	<b>LR3</b> (Remote)	Hi-Lume 1% L3DA EcoSystem 3-wire
40W	24V	120V	<b>LR2</b> (Remote)	Hi-Lume 1% LTEA 2-wire 120V
96W	24V	120V - 277V	<b>LR3</b> (Remote)	Hi-Lume Premier 0.1% EcoSystem/ 3-wire



## ORDERING GUIDE

### Type

**UNV** Universal Driver  
**LUT** Lutron Driver

### Watts

**15** 15 Watts  
**20** 20 Watts  
**40** 40 Watts  
**60** 60 Watts  
**96** 96 Watts

### Output Volts

**24V**  
24V 24 Volts

### Input Volts

**277** 120-277 Volts  
**120** 120 Volts  
(Lutron 2 Wire Driver Only)

### Mounting

**Universal**  
**UIN** Integral  
**URE** Remote

**Lutron**  
**LI2** Integral 2 Wire  
**LI3** Integral 3 Wire  
**LR2** Remote 2 Wire  
**LR3** Remote 3 Wire

Example: UNV-96-24V-277-UIN